

Cura II

Electric profiling bed



The Cura II combines ease of handling and functionality with an attractive design to ensure that it is ideal for community use. Advanced electric profiling adjustments and an easy to use hand set control optimise patient comfort and well-being whilst enhancing patient mobility and independence.

Exceptional electric height range of 250 - 700mm

The Cura II bed ensures that carers are able to work at a comfortable height and avoid static load.

The height range also assists the patient with getting in and out of bed.

Efficient assembly and storage

Quick and easy assembly of the bed can be managed by one person without the use of tools and when not in use the transport and storage system allows the bed to be folded into a compact unit to maximise space

Conforms to highest possible safety standards

The Cura II bed has been independently tested to certify that it is compliant with the latest stability, dimensional and safety requirements of the IEC60601-2-52 Standard.

Integral 200mm bed extension

The mattress platform can be easily extended in situ by 200mm without the need to disassemble the bed. Thus offering maximum flexibility of care and providing a safe comfortable experience for taller patients.



Full length extending side rails



3/4 folding 4-bar side rails



Full length mesh bumpers

The Cura II can be complemented by easily extendable full length telescopic or 3/4 length folding 4-bar side rails.

The side rails are designed to fit the Cura II at a sufficient height to accommodate a typical mattress/ overlay combination to enhance patient safety and feature a safety locking/unlocking mechanism which prevents unintentional activation.

The mesh bumpers are designed to fit neatly onto each extending full length side rail featuring a top and bottom pad, connected by a strong transparent net which concertinas when the side rails are lowered.



Features

- 4-section electric profiling with variable height control adjustments
- Trendelenburg and reverse trendelenburg
- Integral bed extension of 200mm
- Handset control with function lockout
- One-button auto-contour positioning
- Bed easily disassembles into 4 parts for improved transport and installation access
- Compact transport and storage system
- Convenient transport bracket storage underneath bedframe
- Bed platform can be positioned at a height of 250mm above floor level

- Manual calf lift
- Mattress retainers
- Slatted mattress platform
- Individually bracketed castors
- Excellent ground clearance
- Easy to operate individually braked castors
- Optional battery back-up
- Fitted with quality Linak controls and push only actuators
- IEC60601-2-52:2010 compliant
- Maximum patient weight 215kg (34 stone)
- Safe Working Load 250kg (39 Stone)

Accessories

UBEB7002FL-2

Full length extending side rails 2185 - 2385mm

UBEB002001FL-2MESH

Mesh full length side rail bumpers

UBEB002001FL-2MESH-EXT

Mesh full length side rail bumpers extension piece

UBEB7002: 3/4 folding 4 bar side rails

UBEB002001: 3/4 side rail universal bumpers

UBEB7003: Patient lifting pole

UBEB7004-3: In-line Grab Rail (can be used in conjunction with full length and 3/4 length side rails)

UBEB7004: Grab rail - Standard

USPF3408: Mattress extension squab infill



UBEB7002FL-2




UBEB002001FL-2MESH



UBEB7002



UBEB002001



UBEB7003



UBEB7004



UBEB7004-3
in conjunction with full
length extending side rails



UBEB7004-3
in conjunction with
3/4 length side rails



USPF3408

Specification

Product code:	UBEB7001
Overall length:	2185mm
Overall length (extended):	2385mm
Overall width (without side rails):	932mm
Overall width (with removable side rails):	1050mm
Mattress platform:	2000 x 900mm
Mattress platform (extended):	2200 x 900mm
Upper bracket height:	300 - 700mm
Lower bracket height:	250 - 640mm
Height range:	250 - 700mm

Safe working load (SWL):	250kg/ 39 stone
Maximum patient weight:	215kg/ 34 stone
Total bed weight:	81.3kg
Backrest angle:	0 - 70 degrees
Knee-break angle:	0 -33 degrees
Calf rest angle:	5 - 20 degrees
Electrical data	
Power input:	240V ac 50/60HZ
Electric shock protection:	Class II Type B
Ingress protection:	IPX6

For more information on this product please contact us on
tel: 0333 321 8996 or email: sales@ultimatehealthcare.co.uk

www.ultimatehealthcare.co.uk

