

Heritage II Bariatric

Bariatric Dynamic Mattress Replacement



The Heritage II Bariatric dynamic mattress replacement provides optimal care for patients weighing up to 350kg / 55 stone. With a 1200mm width surface and comfort control features the Heritage II Bariatric provides comfortable care options for larger patients considered to be up to a very high risk of pressure damage.



Bariatric pressure area care management

At 1200mm wide the Heritage II Bariatric features a full width deep 8" alternating cell design to provide optimum support and pressure care for larger patients.

Automatic features optimise pressure area care and patient protection whilst reducing the burden on nursing staff. Features such as **Auto-Detection** and **Backrest mode** automatically adjust internal cell pressures to match the patient's weight and position ensuring that they receive optimised care.



Patient safety and real peace of mind

The modern power unit is equipped with advanced **audible and visual alarms** which allow rapid problem diagnostics therefore real peace of mind. An excellent 24-hour **Transport mode** provides a fail-safe to avoid the possibility of bottoming out in the event of a power failure.

An **Auto Control Lockout** feature prevents unintentional activation of the control panel and a **Timed Static mode** which automatically returns to Alternating mode safeguards patients against the risk of pressure damage.



Advanced therapy and care options

Powered by a **dual compressor** the system is able to provide a range of therapies and care for the larger patient. An active 2-cell cycle **Alternating mode** provides pressure redistribution for the prevention and treatment of pressure ulcers.

Constant Low Pressure mode allows the mattress to conform closely a patient's body and redistribute body weight over a wider area; this greater patient immersion delivers optimum constant levels of pressure redistribution.

Features

Power Unit

- Digital control panel
- Dual 9 litres per minute air low
- Comfort control
- Auto-Detection automatic pressure setting
- Variable cycle times (10/15/20/25/30 mins)
- Automatic control panel lockout
- Timed static mode
- Auto-Firm
- Constant Low Pressure (CLP) mode
- Backrest mode
- Transport mode - up to 24 hours
- Audible and visual alarms
- Annual service indicator
- Adjustable hanging brackets

Mattress

- Cell-on-cell construction
- Static head cells
- Lower leg zone
- Premium quality TPU coated nylon cells
- CPR release valve
- Strong cell retention knitted bands
- Maximum patient weight 350kg / 55 stone

Cover

- Soft, waterproof vapour permeable PU cover
- 360 degree zipper
- Welded seams and enclosed zip
- Integral covered air pipe
- Cable management system

Technical Specification

Product code:	UPRA4878-2	Cycle time:	10 / 15 / 20 / 25 / 30 mins (2-cell cycle)
Risk category:	Up to a very high risk	Pressure range:	25-60mmHg
Max user weight:	350 kg / 55 stone	Supply voltage:	230V, 50 Hz
Mattress dimensions:	2000mm x 1200mm x 200mm	Fuse rating:	T1A
Power unit dimensions:	360mm x 130mm x 230mm	Current rating:	0.12 A
Product weight:	10.9kg Mattress / 4.6kg Power Unit	Classification:	Class II, Type BF
Cell material:	TPU	Compliance:	EN 60601-1, EN 60601-1-2
Cover material:	Polyester PU	Warranty:	2 years